

OS-1



Assembly: on: S type poles with B spigot, arm systems, wall brackets KR, columns, extension arms, aluminium or steel wall brackets with Ø60 mm spigot.

Ingress protection: : IP 54

Material: body – fiber glass reinforced PP, UV proof Lamp diffuser– poly(methyl methacrylate) PMMA for transparent and frost, or polycarbonate PC for transparent

Colour: black

Input voltage: 230V AC

Input voltage frequency: 50Hz

Electrical gear cover: mounted on plastic gear tray, magnetic ballast with thermal protection for luminaires 50W-125W, metal halide lamps MH 70W (EL) optionally available with electronic ballast



Sposób montażu: upwards or downwards

Unit volume: 0,01m²

Effective projected area : 0,21m²



Code	Symbol	Power	Lamp diffuser type	Light source type	Exemplary lamp types	Net weight
211202	OS-1 S-70W	70W	Transparent PMMA	Sodium E-27	Philips: SON 70W-E CDO-ET (-TT) 70W Osram: NAV-E 70W	5,2kg
211302	OS-1 S-70W	70W	Transparent PC	Sodium E-27	Philips: SON 70W-E CDO-ET (-TT) 70W Osram: NAV-E 70W	5,2kg
2110002	OS-1 S-70W	70W	Frosted PMMA	Sodium E-27	Philips: SON 70W-E CDO-ET (-TT) 70W Osram: NAV-E 70W	5,2kg
211207	OS-1 MH-70W	70W	Transparent PMMA	Metal halide E-27	Osram: HQI-E 70W	5,2kg
211307	OS-1 MH-70W	70W	Transparent PC	Metal halide E-27	Osram: HQI-E 70W	5,2kg
2110007	OS-1 MH-70W	70W	Frosted PMMA	Metal halide E-27	Osram: HQI-E 70W	5,2kg
211308	OS-1 MH-100W	100W	Transparent PC	Metal halide E-27	Osram: HQI-E 100W	5,4kg
211215	OS-1 E/Z	23W	Transparent PMMA	Compact fluorescent lamp E-27	Philips: 23W / 100W Osram: 23W / 100W	3,9kg
211315	OS-1 E/Z	23W	Transparent PC	Compact fluorescent lamp E-27	Philips: 23W / 100W Osram: 23W / 100W	3,9kg
2110015	OS-1 E/Z	23W	Frosted PMMA	Compact fluorescent lamp E-27	Philips: 23W / 100W Osram: 23W / 100W	3,9kg



Directive: 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE, 2009/125/EC