

# OW



**Assembly:** on columns, extension arms, wall brackets with spigot ending  $\varnothing 42\text{mm}$ , 40mm deep

**Ingress protection:** IP 65

**Material:** base - die cast aluminium cover—poliamide cap—formed aluminium cobntrol gear cover—polycarbonate

**Colour:** black

**Input voltage:** 230V AC


**Input voltage frequency:** 50Hz

**Electrical gear cover:** mounted on universal gear frame, magnetic ballast with thermal protection for luminaires 50W-150W, metal halide lamps MH 70W (EL) optionally available with electronic ballast

**Sposób montażu:** downwards only



Code	Symbol	Diameter of lamp diffuser	Power	Type of diffuser	Light source type	Net weight
210902	OW S-70W k-150	150mm	70W	Sphere 400-450, Cone 400	Sodium E-27	4,6kg
210903	OW S-100W k-150	150mm	100W	Sphere 400-450, Cone 400	Sodium E-40	4,9kg
210907	OW MH-70W k-150	150mm	70W	Sphere 400-450, Cone 400	Metal halide E-27	4,6kg
210908	OW MH-100W k-150	150mm	100W	Sphere 400-450, Cone 400	Metal halide E-27	4,8kg
210915	OW E/Z k-150	150mm	23W	Sphere 400-450, Cone 400	Compact fluorescent lamp E-27	3,2kg
212102	OW S-70W k-150	150mm	70W	Sphere 400-450, Cone 400	Sodium E-27	4,6kg
212103	OW S-100W k-150	150mm	100W	Sphere 400-450, Cone 400	Sodium E-40	4,9kg
212107	OW MH-70W k-150	150mm	70W	Sphere 400-450, Cone 400	Metal halide E-27	4,6kg
212108	OW MH-100W k-150	150mm	100W	Sphere 400-450, Cone 400	Metal halide E-27	4,8kg
212115	OW E/Z k-150	150mm	23W	Sphere 400-450, Cone 400	Compact fluorescent lamp E-27	3,2kg



**Directive:** 2014/35/UE (Official Journal of the UE L 96/357 29.03.2014), 2014/30/UE (Official Journal of the UE L 96/79 29.03.2014), 2011/65/UE, 2009/125/EC