

Aluminium column SAL-P61

diameter Ø180mm at the base plate





Anodising: 10 colours, each with possibility of chemical brightening

Finish: grinded, anodisedaluminium, option of elastomer protection in the colour of the column up to the height of 350 mm (other height on customer's request)

Luminaire mounting: directly on the column, luminaires with mounting Ø60 mm with weight and surface parameters not exceeding the data from the strength table included in the technical data sheet

Extension arm type: According to resistance calculations

Packing: sleeve material



Code	Symbol	Height of the column	Wall thickness	Net weight	Approximate unit volume	Concrete footing / reinforcement basket type	Concrete footing / reinforcement basket code	Fasteners
42487	SAL-P61	9m	4,3mm	59,5kg	0,8m ³	B-70 / Z-70	311170 / 311207	4012

SAL-P61 Acceptable windage of single luminaire [m²] for Cx=0,7

code 42487	Vref. = 22 m/s	Vref. = 24 m/s	Vref. = 26 m/s	Vref. = 28 m/s
Permissible weight of a single luminaire	I zone, II Field category up to	I & III zone, II Field category up to 450m by s.I	II zone, II Field category up to	III zone, II Field category up to 755r by s.I
15	0,38	0,28	0,16	0,12

code 42487	Vref. = 22 m/s	Vref. = 24 m/s	Vref. = 26 m/s	Vref. = 28 m/s
Permissible weight of a single luminaire	I zone, II Field category up to	I & III zone, II Field category up to 450m by s.I	II zone, II Field category up to	III zone, II Field category up to 755r by s.I
15	0,24	0,17	x	x