


# Aluminium column SAL-T11

diameter  $\varnothing 176\text{mm}$  at the base plate



**Anodising:** 10 colours, each with possibility of chemical brightening

**Finish:** grinded, anodised aluminium, option of elastomer protection in the colour of the column up to the height of 350 mm (other height on customer's request)

**Luminaire mounting:** directly on the column, luminaires with mounting  $\varnothing 60\text{mm}$  with weight and surface parameters not exceeding the data from the strength table included in the technical data sheet

**Extension arm type:** According to resistance calculations

**Packing:** sleeve material

Code	Symbol	Height of the kolumn	Wall thickness	Net weight	Approximate unit volume	Concrete footing / reinforcement basket type	Concrete footing / reinforcement basket code	Fasteners
<b>42496</b>	SAL-T11	11,3m	5,2mm	66,3kg	0,76m <sup>3</sup>	B-70 / Z-70	311170 / 311207	4012

SAL-T11

Acceptable windage of single luminaire [m<sup>2</sup>] for Cx=0,7

code 42496	Vref. = 22 m/s	Vref. = 24 m/s	Vref. = 26 m/s	Vref. = 28 m/s
Permissible weight of a single luminaire	I zone, II Field category up to	I & III zone, II Field category up to 450m by s.I	II zone, II Field category up to	III zone, II Field category up to 755m by s.I
15	0,47	0,37	0,26	0,20