


Aluminium column SAL-U1/5

diameter Ø176mm at the base plate

- Anodising:** 10 colours, each with possibility of chemical brightening
- Finish:** grinded, anodisedaluminium, option of elastomer protection in the colour of the column up to the height of 350 mm (other height on customer's request)
- Luminaire mounting:** directly on the column, luminaires with mounting Ø60 mm with weight and surface parameters not exceeding the data from the strength table included in the technical data sheet
- Extension arm type:** According to resistance calculations
- Packing:** sleeve material



Code	Symbol	Height of the column	Wall thickness	Net weight	Approximate unit volume	Concrete footing / reinforcement basket type	Concrete footing / reinforcement basket code	Fasteners
4246515	SAL-U1/5	9,3m	4,3mm	51kg	1,79m³	B-70 / Z-70	311170 / 311207	4012

SAL-U1/5	Acceptable windage of single luminaire [m 2] for Cx=1			
code 4246515	Vref. = 22 m/s	Vref. = 24 m/s	Vref. = 26 m/s	Vref. = 28 m/s
Permissible weight of a single luminaire	I zone, II Field category up to	I & III zone, II Field category up to 450m by s.I	II zone, II Field category up to	III zone, II Field category up to 755m by s.I
15	0,25	0,19	0,12	0,08

