

# Plastic coated poles SP-4W



Code	Name	Spigot type	Height of the column	Net weight	Approximate unit volume	Concrete footing / reinforcement basket type	Concrete footing / reinforcement basket code	Fasteners
<b>17411</b>	SP-4W	A	4,645m	44kg	0,16m <sup>3</sup>	B-40 / Z-40	311140 / 311204	311003
<b>17421</b>	SP-4W	B	4,645m	37kg	0,16m <sup>3</sup>	B-40 / Z-40	311140 / 311204	311003
<b>17451</b>	SP-4W	E	4,645m	50kg	0,17m <sup>3</sup>	B-40 / Z-40	311140 / 311204	311003
<b>17411F</b>	SP-4W	A	4,645m	44kg	0,16m <sup>3</sup>	B-40 / Z-40	311140 / 311204	311003
<b>17421F</b>	SP-4W	B	4,645m	37kg	0,16m <sup>3</sup>	B-40 / Z-40	311140 / 311204	311003
<b>17451F</b>	SP-4W	E	4,645m	50kg	0,17m <sup>3</sup>	B-40 / Z-40	311140 / 311204	311003



**Spigot type „A” – Ø60**

For mounting bracket configuration: type "P",


For mounting extension arms:  
WT, WA-1,WA-01, WA-4



**Spigot type „B” – Ø60**

For mounting the luminaires directly on the pole:

ATLANTIS LED, ELBA, ELBA LED, OP, OPA-1, OS-1, OS-1 LED, OS-11 LED



**Spigot type „E” – Ø60**

For mounting extension arms:  
WTM

